


GRADE 6 - ZİNCİR SAPAN ve AKSESUARLARI


Zincir Sapan Kapasite Tablosu

Zincir ölçüsü	1 bacaklı	2 bacaklı	3 bacaklı	4 bacaklı	Boğma sapanlar
					
	1	1.4 $0^\circ < \beta \leq 45^\circ$ 1 $45^\circ < \beta \leq 60^\circ$	2.1 $0^\circ < \beta \leq 45^\circ$	1.5 $45^\circ < \beta \leq 60^\circ$	1.6
mm	kg	kg	kg	kg	kg
6	900	1250	1890	1350	1440
7	1250	1750	2600	1850	2000
8	1600	2200	3350	2400	2500
10	2500	3500	5250	3750	4000
13	4250	5950	8900	6350	6800
16	6300	8800	13200	9400	10000




C6XC8182 Zincir

Art. No:	Model	Zincir ölçüsü		P	Tolerans	Li min.	Le maks.	Ağırlık	W.L.L	B.F.
		mm	inch							
5650 00 01	C6XC8 18206	6	1/4	18	± 0.5	7.8	22.2	0.8	900	35.3
5650 00 02	C6XC8 18207	7	9/32	21	± 0.6	9.1	25.9	1.1	1250	49.1
5650 00 03	C6XC8 18208	8	5/16	24	± 0.7	10.4	29.6	1.4	1600	62.8
5650 00 04	C6XC8 18210	10	3/8	30	± 0.9	13	37	2.2	2500	98.1
5650 00 05	C6XC8 18213	13	1/2	39	± 1.2	16.9	48.1	3.8	4250	166.8
5650 00 06	C6XC8 18216	16	5/8	48	± 1.4	20.8	59.2	5.7	6300	247.3




C6XCM Masterlink / Bağlantı Halkası

Art. No:	Model	Zincir ölçüsü		D	P	L	Ağırlık	W.LL
		 Ø mm	 Ø mm	mm	mm	mm	kg	0°-45° kg
5650 00 15	C6XCM 07 06	6/7	6	13	110	60	0.34	1600
5650 00 16	C6XCM 08	8	-	13	110	60	0.34	1600
5650 00 17	C6XCM 10 08	10	7-8	16	110	60	0.53	2600
5650 00 18	C6XCM 13 10	13	10	18	135	75	0.80	4250
5650 00 19	C6XCM 16 13	16	13	22	160	90	1.50	6300
5650 00 20	C6XCM 18 16	18	16	26	180	100	2.30	8.900



C6XCMC Masterlink / Bağlantı Halkası

Art. No:	Model	Zincir ölçüsü	D	P	L	D1	P1	L1	Ağırlık	W.L.L.
		$\wedge$ Ø mm	mm	mm	mm	mm	mm	mm	kg	0°-45° kg
5650 00 21	C6XCMC 06	6	13	110	60	10	44	20	0.52	1890
5650 00 22	C6XCMC 07	7	16	110	60	13	54	25	0.97	2600
5650 00 23	C6XCMC 08	8	18	135	75	16	70	34	1.60	3350
5650 00 24	C6XCMC 10	10	22	160	90	18	85	40	2.76	5250
5650 00 25	C6XCMC 13	13	26	180	100	22	115	50	4.450	8900
5650 00 26	C6XCMC 16	16	32	200	110	26	140	65	7.550	13200



C6XCL Bağlantı Elamanı

Art. No:	Model	Zincir ölçüsü		A	C	O	R	P	S	Ağırlık	W.L.L
		mm	inch	mm	mm	mm	mm	mm	mm	kg	kg
5650 00 27	C6XCL 06	6	1/4	14	18	18	45	8	7.5	0.080	900
5650 00 28	C6XCL 07	7	9/32	18	20	20.5	50.5	10.2	9	0.140	1250
5650 00 29	C6XCL 08	8	5/16	19	25.5	23.5	62	11.5	10	0.200	1600
5650 00 30	C6XCL 10	10	3/8	24	30	27.5	72	12.6	12.6	0.350	2500
5650 00 31	C6XCL 13	13	1/2	28	36	33.5	87.5	19	16.7	0.730	4250
5650 00 32	C6XCL 16	16	5/8	34.5	40.5	39.5	105	20.6	20.6	1.470	6300