

GRADE 8 - ZİNCİR SAPAN ve AKSESUARLARI

Zincir Sapan Kapasite Tablosu

Zincir ölçüsü	1 bacaklı	2 bacaklı		3 - 4 bacaklı		Boğma sapanlar		Çember sapanlar
				 				
	1	1.4 0° < β ≤ 45°	1 45° < β ≤ 60°	2.1 0° < β ≤ 45°	1.5 45° < β ≤ 60°	1.6	1.4 0° < β ≤ 45°	2.1 0° < β ≤ 45°
mm	kg	kg	kg	kg	kg	kg	kg	kg
6	1120	1600	1120	2360	1700	1800	1600	2360
7	1500	2120	1500	3150	2240	2500	2120	3150
8	2000	2800	2000	4250	3000	3150	2800	4250
10	3150	4250	3150	6700	4750	5000	4250	6700
13	5300	7500	5300	11200	8000	8500	7500	11200
16	8000	11200	8000	17000	11800	12500	11200	17000
20	12500	17000	12500	26500	19000	20000	17000	26500
22	15000	21200	15000	31500	22400	23600	21200	31500
26	21200	30000	21200	45000	31500	33500	30000	45000
32	31500	45000	31500	67000	47500	50000	45000	67000

C Zincir



Art. No:	Model	Zincir ölçüsü		P	Tolerans	Li min.	Le maks.	Ağırlık	W.L.L	M.P.F	B.F.	f min.
		mm	inc	mm	mm	mm	mm	kg / m	kg	KN	KN	mm
5890 00 06	C 06	6	1/4	18	± 0.5	7.8	22.2	0.8	1120	28.3	45.2	4.8
5890 00 07	C 07	7	9/32	21	± 0.6	9.1	25.9	1.1	1500	38.5	61.6	5.6
5890 00 08	C 08	8	5/16	24	± 0.7	10.4	29.6	1.4	2000	50.3	80.4	6.4
5890 00 10	C 10	10	3/8	30	± 0.9	13	37	2.2	3150	78.5	126	8
5890 00 13	C 13	13	1/2	39	± 1.2	16.9	48.1	3.8	5300	133	212	10
5890 00 16	C 16	16	5/8	48	± 1.4	20.8	59.2	5.7	8000	201	322	13
5890 00 20	C 20	20	3/4	60	± 1.8	26	74	9	12500	314	503	16
5890 00 22	C 22	22	7/8	66	± 2.0	28.6	81.4	10.9	15000	380	608	18
5890 00 26	C 26	26	1	78	± 2.3	33.8	96.2	15.2	21200	531	849	21
5890 00 32	C 32	32	1 1/4	96	± 2.9	41.6	118	23	31500	804	1290	26
5890 00 36	C 36	36	-	108	-	46.8	133	29	40000	1020	1630	-

EN 818-4 Emniyet kat sayısı 4:1

KESKİN KÖŞE UYGULAMASI ve KAPASİTE KAYBI

Zincir Köşe Kullanımı	R ≥ zincir çapı x 2	R ≥ Tek zincir çapı	Keskin köşe
Kapasite kaybı	1	0,7	0,5

Darbesele yük	Hafif darbe	Orta darbe	Ağır darbe
Kapasite kaybı	1	0,7	Kullanılamaz

ZİNCİR SAPAN KULLANIM ÖRNEKLERİ

